(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 4 November 2004 (04.11.2004)

PCT

(10) International Publication Number WO 2004/095056 A1

(51) International Patent Classification⁷: 11/14, 5/18, 5/20, 5/24

G01S 5/30,

(21) International Application Number:

PCT/IB2004/050465

(22) International Filing Date: 16 April 2004 (16.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03101098.6

22 April 2003 (22.04.2003) EF

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VAN LOENEN, Evert, J. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DIJK, Esko, O. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN BERKEL, Cornelis, H. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


- (74) Agent: GROENENDAAL, Antonius, W., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: OBJECT POSITION ESTIMATION SYSTEM, APPARATUS AND METHOD



6 (57) Abstract: The position estimation system (220, 226, 222) for estimating a position of an object (224) in a room (200) works by an ultrasound emitter (220) emitting an ultrasound pulse (201), which is reflected at least once on a reflecting object (232), after which an ultrasound receiver (226) detects an ultrasound signal (300) comprising at least the reflection and possibly also a line of sight transmission. Either the emitter or the receiver is attached to the object. A processor estimates the position of the object (224) on the basis of the ultrasound signal (300), by a calculation dependent on properties of the ultrasound signal (300) or by matching the ultrasound signal (300) with templates for object (224) positions, obtained by measurement or by simulation of the ultrasound pulse (201) transmission in the room (200).



WO 2004/095056 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.